

Directory Search Results

WRAS Approval Number: 2209348

Approved Product

Range of single hole, single outlet (fixed) combination tap assemblies incorporating a brass body and ceramic cartridge headworks with single lever operating members. The spout outlet incorporates a plastic aerator. Maximum working pressure 5.0 bar. Maximum operating temperature 65°C.

Section: 0450 Combination Tap Assemblies (?section=0450)

Section Subtitle: Single hole, metal single outlet, fixed. Taps used in high risk installations, such as kitchen sinks, are considered to be a fluid category 5 risk. Backflow protection is usually provided in the form of an AUK3 tap gap. Where an AUK3 tap gap cannot be maintained, for example where the tap gap is compromised as a result of: • the tap being lowered in any way; • adjustment to the spout which reduces the distance between the tap outlet and spillover level of the sink; • or the operation of a pull out hose attachment; alternative fluid category 5 backflow protection is required.

WRAS Approval Number: 2209348

Expiry date: 30/09/2027

Note: R009 does not apply to PEX hoses

Size: Stainless-steel braided PEX lined flexible hose assemblies with ½" BSP captive nut end connections.

Marking: HB on body.

Installation Requirements: R001 (/approvals/testing-requirements/installation_requirements/irn_r001)R006 (/approvals/testing-requirements/installation_requirements/irn_r006)R010 (/approvals/testing-requirements/installation_requirements/irn_r010)

Model: NU-031, NU-038, NU-032 & NU-039

Factor: Harrison Bathrooms Incorporating Scudo
View All Listings by this Company (?company=19358)